



WE-JMPR 510A

Mobile 5 Bands x 2Watt Remote Controlled Jammer

The WE-JMPR 510A can be applied at meeting room, conference room, museum, gallery, theatre, concert hall, church, temple, restaurant, classroom, training center, factory, bank, train, bus, etc.

easy to install and operate the device. No adjustment is needed.

The WE-JMPR 510A is installed in waterproof Pelican Case and can be operated locally and remotely .

Include 5 external Dipoles omni direction antennas and 6V DC adaptor / charger

Specifications

- * **Tx Frequency**
870-885 MHz
925/935-960 MHz
1805-1850 MHz
1975-1980 MHz
2100-2170 MHz
- * **Cover interface standards**
Digital CDMA, GSM, UMTS, CDMA1900
Analog: AMPS, NMT, N-AMPS, TACS
- * **Total output power**
10W (800 : 2W, 900 : 2W , 1805: 2W, 1900: 2W , 2100: 2W)
- * **Signal Source**
PLL synthesized
- * **Continue using time**
90 minutes with battery and continuously when plugged to 110V-220Volt Power
- * **All the TX frequency covered down link only**
- * **Auto atic power switching power supply**
50 / 60 Hz / AC 100 ~ 240V transmitting to DC 5V
- * **Working temperature**
-10C - +60C With thermostat cooling fan
- * **Jamming range**
Radius 20~30 M 【 the signal must < -80dBm in the location 】 The jamming radius still depends on the strength signal in given area
- * **Safety regulation**
AC Adapter UL (E190582), CSA (LR112971 Level 3)

Carcom 5 Modeen Israel

Tel: +972-57-6550444 Fax: +972-57-1534954389 Mobile: +972-57-4954389

Site: www.wiseeye.co.il mail: office@wiseeye.co.il